

NEW

ArcticChill 108

Exceptional Dispense Height of 29cm

- The ArcticChill108 is identical to the very successful ArcticChill88. The main change is a new upper front panel with an increased dispensing height to 29cm.
- Single Dispensing Button for Chilled Only
- High Capacity Direct Chill Cold Water
- FloodGuard inlet solenoid flood protection
- Can be fitted with Overflow Kits & Mains Drainage
- Fits AA Cooler Cowling & Wall Bracket
- Stylish design in Anthracite livery



Delivers 30 – 40 Ltr per Hour Of Chilled Water, Below 12C

For optimum flow rate the mains water pressure at the point of entry into the Cooler should be around 3.5 bar.

Accessories For The ArcticChill 108

Installation rail with filter. Includes compression fitting, 1-Micron green filter, water block, copper pressure reducing valve & non-return valve.



FloodGuard - closed inlet solenoid only opens to allow water into the cooler, when water is dispensed. By remaining closed all other times it protects the cooler against leaks.



The KLARAN UVC LED Shield protects Direct Chill Water Coolers from Bacteria, Viruses & other Pathogens providing point of dispense protection. Factory Fitted or Self Installed options.



Mains drainage - connect the drip tray to mains drainage.



Can also be supplied with pumped waste if mains drainage is not available.

3 Litre overflow kit connects the drip tray to a 3 litre alarmed overflow container.



10 litre overflow system with alarm to signal when full. (Factory fitted)



Description	Dimensions H x W x D (MM)	Weight (Kg)
Floor Standing	1140 x 340 x 350	25
Table Top	460 x 340 x 340	16

AAFIRST

Quality – Reliability – Integrity